



TIGG 5D 1240

Virgin Liquid Phase Coal Based Activated Carbon

DESCRIPTION

TIGG 5D 1240 is a granular activated carbon made from selected grades of bituminous coal. The range of pore sizes can accommodate organic molecules of varied size. The higher adsorption energy pores of this activated carbon permit the attainment of 100% removal of most organics from water and other liquids.

TYPICAL PROPERTIES	TIGG 5D 1240
U.S Sieve, 90 wt% min	12 x 40*
Iodine Number, mg/g, min	950
Apparent Density, (dense packing)	
g/cc	0.43 - 0.48
lbs/ft ³	27 - 30
Moisture - wt% max (as packed)	3
Hardness No. - min	95
Abrasion No. min	80

* Size 0830 is also available

TYPICAL APPLICATIONS

This activated carbon can be used to remove :

- BTEX and other organic compounds from ground water
- Organic compounds from wastewater
- Organic compounds from potable water
- Trace organics from process streams such as alcohols, glycerine, MEA, acids, etc.

Standard packaging of the activated carbon is in 55 pound bags or 1100 pound supersacks.

Wet drained activated carbon adsorbs oxygen from the air. Therefore, when workers need to enter a vessel containing wet activated carbon, they should follow confined space/low oxygen level procedures. Activated carbon dust does not present an explosion hazard.