



Two diesel and one gasoline tanks were removed from the Lowe Farm site in Limestone County, Alabama, raising concerns about petroleum hydrocarbon and BTEX contamination. Newterra's ozone injection remediation plan successfully reduced BTEX levels

Case Study: Newterra Technology has been selected to develop a remediation plan for soil and groundwater contaminated with petroleum hydrocarbons and BTEX

Summary

One gasoline and two diesel USTs were removed from the Lowe Farm site in July 1995, which is located in Limestone County, Alabama. The Alabama Department of Environmental Management (ADEM) required that investigative and corrective actions be implemented at the site. PPM Consultants Inc.'s (PPM) services were requested to construct a corrective action plan for the site by the property owner. In general, the native lithology is such that the upper 25 feet of soil consists of moist, reddish brown clay and silty or sandy clay. Chert fragments were present in most of the borings at various depths. Primary contaminants of concern are petroleum hydrocarbon and BTEX residual in both the soil and groundwater.

The Solution


Newterra was selected as the remediation technology for this site. After initial site condition research was conducted and a system sizing questionnaire was filled out, Newterra recommended the use of an OSU20-52 cabinet with 10 insitu oxidation points, each estimated at achieving a 10 foot radius of influence. The site layout shows the locations of each of the sparge wells.

The Results

Sparging began in December of 2006. Results from monitoring indicated that BTEX levels dramatically decreased from the time that the system was installed. Results from monitoring well 8 are graphed showing the fluctuating background concentrations pre ozone and the decreasing trends from throughout the injection period. The site closed in 2008.

Project Snapshot

Existing Conditions: Primary contaminants of concern are petroleum hydrocarbon and BTEX residual in both the soil and groundwater.



The Newterra Solution: Newterra was contracted to build a system capable of injecting concentrated ozone gas focussed on treating BTEX and Benzene in tight clay soils. Newterra recommended the use of an 10 pound per day ozone cabinet equiped with Intelo-zone. The system utilized 10 in-situ oxidation points, each estimated at achieving a 10 foot radius of influence.

Contaminant	Soil (ppm)	Groundwater (ppm)
Benzene	0.54 14.80	14.80
Toluene	0.24	22.30
Ethyl-benzene	2.02	2.11
Xylene	9.17	12.40
MTBE	0.04	0.09

The site was closed in a year and a half after mobiliziation.


What's Your Unique Water Question?

Contact us today at +1800.420.4056 to solve your most challenging water issue. Our experts are here to solve your water problems by tailoring solutions based on your operational, regulatory and safety goals.






With Newterra, it's more than a service; it's a partnership... minimizing media consumption and maximizing efficiency. 99















From Source to Solution - Choose Newterra

Your trusted partner for comprehensive environmental solutions

With technology brands whose histories expand back for more than 150 years, Newterra has steadily grown from its roots to become a global solutions provider in water and wastewater treatment. Our journey is a testament to our deep understanding of the multifaceted challenges across various markets and applications.

Our "One Newterra" ethos is a commitment to providing a comprehensive array of technical solutions, ensuring we address the full spectrum of our clients' needs. This dedication extends beyond technology, as we nurture enduring partnerships with our clients, standing by them throughout every phase of their challenges. At the heart of Newterra is our unwavering commitment to sustainability.

Our people, our technologies and our practices contribute meaningfully to a sustainable and brighter future.



